



1 Identification

- **Product identifier**
- **Trade name:** Steelkote 147 Jet Black
- **Article number:** 147B100
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Baril Coating USA, LLC
401 Growth Parkway
Angola, IN 46703
- **Information department:** Product safety department
- **Emergency telephone number:** During normal opening times: +1 (260) 665-8431

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

Trade name: Steelkote 147 Jet Black

(Contd. of page 1)

· **Hazard-determining components of labeling:**

4-methylpentan-2-one

n-butyl acetate

Solvent naphtha (petroleum), light arom.

Carbon black

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

· **Hazard statements**

Highly flammable liquid and vapor.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = *2

Fire = 3

Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.

(Contd. on page 3)

Printing date 10/21/2024

Reviewed on 10/21/2024

Trade name: Steelkote 147 Jet Black

(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Hazardous substances listed below.

- **Dangerous components:**

123-86-4	n-butyl acetate	>10-<20%
540-88-5	tert-butyl acetate	>2.5-≤10%
110-43-0	Methyl n-amyl ketone	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
79-20-9	methyl acetate	>2.5-<10%
108-10-1	4-methylpentan-2-one	>2.5-<10%
1333-86-4	Carbon black	0.1-≤2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	0.1-≤2.5%
100-41-4	ethylbenzene	0.1-≤2.5%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	0.1-≤2.5%
64-17-5	ethanol	0.1-≤2.5%
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.1-<1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

US

Trade name: Steeltote 147 Jet Black

(Contd. of page 3)

Environmental precautions:

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

Protective Action Criteria for Chemicals**PAC-1:**

123-86-4	<i>n</i> -butyl acetate	5 ppm
540-88-5	<i>tert</i> -butyl acetate	600 ppm
110-43-0	Methyl <i>n</i> -amyl ketone	150 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
79-20-9	methyl acetate	250 ppm
108-10-1	4-methylpentan-2-one	75 ppm
1333-86-4	Carbon black	9 mg/m ³
628-63-7	pentyl acetate	100 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m ³
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
64-17-5	ethanol	1,800 ppm

PAC-2:

123-86-4	<i>n</i> -butyl acetate	200 ppm
540-88-5	<i>tert</i> -butyl acetate	1,700 ppm
110-43-0	Methyl <i>n</i> -amyl ketone	670 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
79-20-9	methyl acetate	1,700 ppm
108-10-1	4-methylpentan-2-one	500 ppm
1333-86-4	Carbon black	99 mg/m ³
628-63-7	pentyl acetate	670 ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m ³
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
64-17-5	ethanol	3300* ppm

PAC-3:

123-86-4	<i>n</i> -butyl acetate	3000* ppm
540-88-5	<i>tert</i> -butyl acetate	10,000 ppm
110-43-0	Methyl <i>n</i> -amyl ketone	4000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm

(Contd. on page 5)

Printing date 10/21/2024

Reviewed on 10/21/2024

Trade name: Steelkote 147 Jet Black

(Contd. of page 4)

79-20-9	methyl acetate	10000* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
1333-86-4	Carbon black	590 mg/m ³
628-63-7	pentyl acetate	4000* ppm
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m ³
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
64-17-5	ethanol	15000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

540-88-5 tert-butyl acetate

PEL	Long-term value: 950 mg/m ³ , 200 ppm
REL	Long-term value: 950 mg/m ³ , 200 ppm

(Contd. on page 6)

Printing date 10/21/2024

Reviewed on 10/21/2024

Trade name: Stealkote 147 Jet Black

(Contd. of page 5)

TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm
-----	--

110-43-0 Methyl n-amyl ketone

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 233 mg/m ³ , 50 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

79-20-9 methyl acetate

PEL	Long-term value: 610 mg/m ³ , 200 ppm
REL	Short-term value: 760 mg/m ³ , 250 ppm Long-term value: 610 mg/m ³ , 200 ppm
TLV	Short-term value: 757 mg/m ³ , 250 ppm Long-term value: 606 mg/m ³ , 200 ppm

108-10-1 4-methylpentan-2-one

PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

64-17-5 ethanol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm

Ingredients with biological limit values:**108-10-1 4-methylpentan-2-one**

BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----	--

(Contd. on page 7)

US

Trade name: **Steelkote 147 Jet Black**

(Contd. of page 6)

100-41-4 ethylbenzene

BEI	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	
	Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
Form: Liquid

(Contd. on page 8)

Printing date 10/21/2024

Reviewed on 10/21/2024

Trade name: Steelkote 147 Jet Black

(Contd. of page 7)

· Color:	Black
· Odor:	Solvent-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	57 °C (134.6 °F)
· Flash point:	10 °C (50 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm ³ (8.35 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Miscible
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	35.9 %
VOC content:	35.87 %
	358.7 g/l / 2.99 lb/gal
· Solids content:	50.7 % (by weight)
· Other information:	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 9)

US

Trade name: **Steelkote 147 Jet Black**

(Contd. of page 8)

· **Hazardous decomposition products:** No dangerous decomposition products known.**11 Toxicological information**· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)

· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** No irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Carcinogenic.

The product can cause inheritable damage.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

108-10-1	4-methylpentan-2-one	2B
1333-86-4	Carbon black	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

(Contd. on page 10)

Printing date 10/21/2024

Reviewed on 10/21/2024

Trade name: Steelkote 147 Jet Black



(Contd. of page 9)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|----------------------------|
| · UN-Number | UN1263 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Paint |
| · DOT | PAINT |
| · IMDG, IATA | |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | II |
| · DOT, IMDG, IATA | |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Flammable liquids |
| · Danger code (Kemler): | 33 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | B |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 11)

US

Printing date 10/21/2024

Reviewed on 10/21/2024

Trade name: Steelkote 147 Jet Black

(Contd. of page 10)

· **Transport/Additional information:**· **DOT**· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **IMDG**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, II

15 Regulatory information· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-10-1 4-methylpentan-2-one

1330-20-7 xylene

100-41-4 ethylbenzene

· **TSCA (Toxic Substances Control Act):**

123-86-4 n-butyl acetate

540-88-5 tert-butyl acetate

110-43-0 Methyl n-amyl ketone

108-65-6 2-methoxy-1-methylethyl acetate

79-20-9 methyl acetate

108-10-1 4-methylpentan-2-one

1333-86-4 Carbon black

628-63-7 pentyl acetate

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

64742-95-6 Solvent naphtha (petroleum), light arom.

1330-20-7 xylene

100-41-4 ethylbenzene

624-41-9 2-methylbutyl acetat

64742-48-9 Naphtha (petroleum), hydrotreated heavy

104810-47-1 poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-

104810-48-2 poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxy-

64-17-5 ethanol

41556-26-7 Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

82919-37-7 methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate

(Contd. on page 12)

Trade name: Steelkote 147 Jet Black

(Contd. of page 11)

· **Proposition 65**· **Chemicals known to cause cancer:**

108-10-1	4-methylpentan-2-one
1333-86-4	Carbon black
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-10-1	4-methylpentan-2-one
64-17-5	ethanol

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

108-10-1	4-methylpentan-2-one	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

1333-86-4	Carbon black	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
64-17-5	ethanol	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word Danger**· **Hazard-determining components of labeling:**

4-methylpentan-2-one
 n-butyl acetate
 Solvent naphtha (petroleum), light arom.
 Carbon black
 Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

· **Hazard statements**

Highly flammable liquid and vapor.
 May cause an allergic skin reaction.
 May cause genetic defects.
 May cause cancer.
 May cause drowsiness or dizziness.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.

(Contd. on page 13)

Trade name: Steelkote 147 Jet Black

(Contd. of page 12)

Read label before use.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** Mr. Williams

- **Date of preparation / last revision** 10/21/2024 / -

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

(Contd. on page 14)

Printing date 10/21/2024

Reviewed on 10/21/2024

Trade name: Steelkote 147 Jet Black

(Contd. of page 13)

*Flam. Liq. 2: Flammable liquids – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**Muta. 1B: Germ cell mutagenicity – Category 1B**Carc. 1A: Carcinogenicity – Category 1A**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

— US —