

Page 1/11

## Safety Data Sheet acc. to OSHA HCS


Printing date 07/01/2024

Reviewed on 01/16/2024

## 1 Identification

- · Product identifier
- · Trade name: <u>Activator 096</u>
- · Article number: ACT096
- · Details of the supplier of the safety data sheet
- *Manufacturer/Supplier:* Baril Coatings USA 401 Growth Parkway Angola, IN 46703
- *Information department:* Product safety department • *Emergency telephone number:* During normal opening times: +1 (260) 665-8431

## 2 Hazard(s) identification



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS08 Health hazard

Muta. 1BH340May cause genetic defects.Carc. 1BH350May cause cancer.

GHS07

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335 May cause respiratory irritation.

## · Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS). *Hazard pictograms*



(Contd. on page 2)

us

Page 2/11

Printing date 07/01/2024

#### Trade name: Activator 096

Safety Data Sheet acc. to OSHA HCS Reviewed on 01/16/2024

(Contd. of page 1)

Signal word Danger	(Contd. of page 1)
Signal word Danger	
Hazard-determining components of labeling:	
Methyl n-amyl ketone	
Hexamethylene Diisocyanate Homopolymer	
Solvent naphtha (petroleum), light arom.	
1,2,4-trimethylbenzene	
Hazard statements	
Highly flammable liquid and vapor. Harmful if inhaled.	
Causes skin irritation.	
May cause genetic defects.	
May cause generic delects. May cause cancer.	
May cause cancer. May cause respiratory irritation.	
Precautionary statements	
f medical advice is needed, have product container or label at hand.	
Keep out of reach of children.	
Read label before use.	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
f on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/s	shower.
F INHALED: Remove person to fresh air and keep comfortable for breathing.	
F exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
f skin irritation occurs: Get medical advice/attention.	
n case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regu	ılations.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 1	
3 Fire = 3	
$\frac{1}{10} Reactivity = 0$	
HMIS-ratings (scale 0 - 4)	
HEALTH <sup>*2</sup> Health = *2	
FIRE 3 Fire = 3	
REACTIVITY [0] Reactivity = 0	
Other hazards	
Results of PBT and vPvB assessment	
PBT: Not applicable.	(Contd. on page 3)

(Contd. on page 3)

### Trade name: Activator 096

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/16/2024

• **vPvB:** Not applicable.

(Contd. of page 2)

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

<sup>.</sup> Dangerous	components:	
28182-81-2	Hexamethylene Diisocyanate Homopolymer	60.74%
	Methyl n-amyl ketone	24.51%
540-88-5	tert-butyl acetate	8.76%
123-86-4	n-butyl acetate	3.33%
64742-95-6	Solvent naphtha (petroleum), light arom.	1.33%
95-63-6	1,2,4-trimethylbenzene	1.33%

## 4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

Information for doctor:

- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed* No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

<sup>-</sup> US

## Trade name: Activator 096

Reviewed on 01/16/2024

		(Contd. of page
	ective authorities in case of seepage into water course or sewage system.	
	to enter sewers/ surface or ground water.	
	nd material for containment and cleaning up:	
	liquid-binding material (sand, diatomite, acid binders, universal binders, saw	/dust).
	ntaminated material as waste according to item 13.	
	quate ventilation. with water or aqueous cleansing agents	
	o other sections	
	7 for information on safe handling.	
	8 for information on personal protection equipment.	
	13 for disposal information.	
	Action Criteria for Chemicals	
PAC-1:		
	Hexamethylene Diisocyanate Homopolymer	7.8 mg/m <sup>3</sup>
	Methyl n-amyl ketone	150 ppm
540-88-5	tert-butyl acetate	600 ppm
	n-butyl acetate	5 ppm
95-63-6	1,2,4-trimethylbenzene	140 ppm
PAC-2:		
28182-81-2	Hexamethylene Diisocyanate Homopolymer	86 mg/m³
110-43-0	Methyl n-amyl ketone	670 ppm
540-88-5	tert-butyl acetate	1,700 ppm
	n-butyl acetate	200 ppm
95-63-6	1,2,4-trimethylbenzene	360 ppm
PAC-3:		
28182-81-2	Hexamethylene Diisocyanate Homopolymer	510 mg/m <sup>3</sup>
110-43-0	Methyl n-amyl ketone	4000* ppm
540-88-5	tert-butyl acetate	10,000 ppm
	n-butyl acetate	3000* ppm
95-63-6	1,2,4-trimethylbenzene	480 ppm

## 7 Handling and storage

· Handling:

- Precautions for safe handling
   Ensure good ventilation/exhaustion at the workplace.
   Open and handle receptacle with care.
   Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
   Keep respiratory protective device available.
- <sup>•</sup> Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 5)

<sup>·</sup>US

Page 5/11

Printing date 07/01/2024

Trade name: Activator 096

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/16/2024

(Contd. of page 4)

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

110-4	43-0 Methyl n-amyl ketone	
PEL	Long-term value: 465 mg/m <sup>3</sup> ,	100 ppm

REL Long-term value: 465 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 233 mg/m<sup>3</sup>, 50 ppm

#### 540-88-5 tert-butyl acetate

- PEL Long-term value: 950 mg/m<sup>3</sup>, 200 ppm
- REL Long-term value: 950 mg/m<sup>3</sup>, 200 ppm TLV Short-term value: 712 mg/m<sup>3</sup>, 150 ppm
  - Long-term value: 238 mg/m³, 50 ppm

## 123-86-4 n-butyl acetate

- PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppm REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm
- Long-term value: 710 mg/m³, 150 ppm
- TLV Short-term value: 712 mg/m<sup>3</sup>, 150 ppm Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

# 95-63-6 1,2,4-trimethylbenzene

REL Long-term value: 125 mg/m<sup>3</sup>, 25 ppm

TLV Long-term value: 123 mg/m<sup>3</sup>, 25 ppm

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

Reviewed on 01/16/2024

#### (Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

General Information	
Appearance:	
Form:	Liquid
Color:	Clear Dahart like
Odor:	Solvent-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	97.9 °C (208.2 °F)
Flash point:	15 °C (59 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	480 °C (896 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	5.5 Vol %
Vapor pressure at 20 °C (68 °F):	6 hPa (4.5 mm Hg)
Density at 20 °C (68 °F):	1 g/cm³ (8.35 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

Reviewed on 01/16/2024

		(Contd. of page 6
<ul> <li>Solubility in / Miscibility with Water:</li> </ul>	Miscible	
Partition coefficient (n-octano	/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	30.5 %	
VOC content:	30.50 %	
	305.0 g/l / 2.55 lb/gal	
Solids content:	60.7 % (by weight)	
· Other infomation:	No further relevant information available.	

## 10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

28182-81-2 Hexamethylene Diisocyanate Homopolymer

Oral LD50 >5,000 mg/kg (rat)

Inhalative LC50/4 h 0.554 mg/l (rat)

		• • • /
110-43-0	Methyl n-a	myl ketone
Oral	LD50	1,670 mg/kg (rat)
Dermed		10 600 marillia (rahhit)

-	64742-95-	6 Solvent	naphtha (petroleum), light arom.
	Dermai	LD50	12,600 mg/kg (rabbit)

-	 	· · · · · · · · · · · /
Oral	LD50	>6,800 mg/kg (rat)

- Dermal LD50 >3,400 mg/kg (rab)
- Inhalative LC50/4 h >10.2 mg/l (rat)
  - 95-63-6 1,2,4-trimethylbenzene
  - Oral LD50 5,000 mg/kg (rat)
  - · Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

· on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

(Contd. on page 8)

US

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/16/2024

(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/16/2024

		(Contd. of page 8
· IMDG, IATA	PAINT	
· Transport hazard class(es)		
·DOT		
LAMMARE LOUD		
· Class	3 Flammable liquids	
·Label	3	
·IMDG		
<sup>.</sup> Class	not regulated	
<sup>.</sup> Label	3	
· Class · Label	3 Flammable liquids 3	
	3	
· Packing group · DOT, IMDG, IATA	II	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Warning: Flammable liquids	
EMS Number:	F-E, <u>S-E</u>	
Stowage Category	В	
<ul> <li>Transport in bulk according to Ann MARPOL73/78 and the IBC Code</li> </ul>	nex II of Not applicable.	
	UN 1263 PAINT, 3, II	

# 15 Regulatory information

 $^{\cdot}$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $^{\cdot}$  Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

95-63-6 1,2,4-trimethylbenzene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 10)

US ·

## Trade name: Activator 096

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/16/2024

(Contd. of page 9)

 $\Pi$ 

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

95-63-6 1,2,4-trimethylbenzene

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

## · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Danger · Hazard-determining components of labeling: Methyl n-amyl ketone Hexamethylene Diisocyanate Homopolymer Solvent naphtha (petroleum), light arom. 1,2,4-trimethylbenzene · Hazard statements Highly flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. May cause genetic defects. May cause cancer. May cause respiratory irritation. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

(Contd. on page 11)

## Trade name: Activator 096

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/16/2024

 $(C_{C})$ ntd of n 10)

(Contd. of page 10) only outdoors or in a well-ventilated area.
ar protective gloves/protective clothing/eye protection/face protection.
skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IHALED: Remove person to fresh air and keep comfortable for breathing.
xposed or concerned: Get medical advice/attention.
a poison center/doctor if you feel unwell.
cific treatment (see on this label).
e off contaminated clothing and wash it before reuse.
in irritation occurs: Get medical advice/attention.
ase of fire: Use for extinction: CO2, powder or water spray.
e in a well-ventilated place. Keep container tightly closed.
e in a well-ventilated place. Keep cool.
e locked up.
bose of contents/container in accordance with local/regional/national/international regulations.
ional regulations:
rmation about limitation of use:
kers are not allowed to be exposed to the hazardous carcinogenic materials contained in this
paration. Exceptions can be made by the authorities in certain cases.
mical safety assessment: A Chemical Safety Assessment has not been carried out.
inical salety assessment. A onemical salety Assessment has not been carried out.
ner information
information is based on our present knowledge. However, this shall not constitute a guarantee for
specific product features and shall not establish a legally valid contractual relationship.
artment issuing SDS: Environment protection department.
tact: Mr. Williams
e of preparation / last revision 07/01/2024 / -
reviations and acronyms:
6: International Maritime Code for Dangerous Goods
US Department of Transportation
: International Air Transport Association
IH: American Conference of Governmental Industrial Hygienists CS: European Inventory of Existing Commercial Chemical Substances
CS: European List of Notified Chemical Substances
Chemical Abstracts Service (division of the American Chemical Society)
A: National Fire Protection Association (USA)
S: Hazardous Materials Identification System (USA)
: Volatile Organic Compounds (USA, EU)
2: Lethal concentration, 50 percent 2: Lethal dose, 50 percent
Persistent, Bioaccumulative and Toxic
: very Persistent and very Bioaccumulative
H: National Institute for Occupational Safety
A: Occupational Safety & Health
Threshold Limit Value
Permissible Exposure Limit Recommended Exposure Limit
. Liq. 2: Flammable liquids – Category 2
e Tox. 4: Acute toxicity – Category 4
Irrit. 2: Skin corrosion/irritation – Category 2
. 1B: Germ cell mutagenicity – Category 1B
Irrit. 2: Skin corrosion/irritation – Category 2 . 1B: Germ cell mutagenicity – Category 1B 1B: Carcinogenicity – Category 1B T SE 3: Specific target organ toxicity (single exposure) – Category 3