



## TECHNICAL DATASHEET

### WAX CAVITY PROTECTION

**ART. NO:** #126.061 (500ml)

WAX CAVITY PROTECTION is a special anti-rust conservation coating designed for long-lasting protection against corrosion in vehicle cavities. Due to its excellent penetrating properties, the product will remove humidity and even water that exists in the narrowest corners and folds. Will not drip or run thanks to its unique formula and 24" applicator wand.

#### FEATURES

- ✓ Prevents rust
- ✓ Protects against corrosion
- ✓ Renews existing protective coatings
- ✓ Easily accesses hard to reach areas
- ✓ Removes water and humidity
- ✓ Temperature stable up to 80°C

#### APPLICATION

Ideal for renewing and retouching existing protective coatings found in vehicle cavities.

#### CONDITIONS OF USE AND CONFORMITY

*The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.*

#### HEALTH & SAFETY

**See Safety Data Sheet and labels for additional safety information and handling instructions.** Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

#### CAUTION

**CAN BE PROCESSED AT ANY TEMPERATURE. DO NOT SPRAY ON THE MOTOR, GEARS, BRAKES, ETC.**

#### HANDLING

1. Clean the repair area ensuring that the surface is clean and free of grease.
2. Shake well for about 3 minutes before using. Apply generously in order to achieve a recommended thickness of approximately 40 µm.
3. Clean the nozzle after use by turning the spray can upside down and spraying until the valve is clean.

#### PRODUCT DATA

**Color:** Brown-yellow

**Salt Drizzle Test (DIN 50021):** 1500 hours

**Drying Time (20°C):** 5 hours

**Shelf Life:** 2 years sealed in original container

**Storage:** Keep between 10 - 30°C. Protect from heat and direct sunlight.

**Package:** 500 ml + 24" applicator wand

**Number per case:** 6

*Safety Data Sheet (SDS) is available on our website*