

# Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 09-16-2015

Replaces:



## 1. Identification

**Product Name:** Durabuild Gray  
**Product identifier:** 102274  
**Relevant identified uses of the substance or mixture and uses advised against:** Acrylic Primer Surfacers

**Chemical Manufacturer / Importer / Distributor:** ITW Evercoat  
a division of Illinois Tool Works Inc.  
6600 Cornell Road  
Cincinnati, OH 45242  
513-489-7600  
**Emergency telephone number:** CHEMTREC: 1-800-424-9300  
CANUTEC: 1-613-996-6666

## 2. Hazard(s) identification

**Classification of the chemical in accordance with paragraph (d) of §1910.1200;**

**GHS Hazard Symbols:**



**GHS Classification:**

Serious Eye Damage/Eye Irritation Category 1  
Skin Corrosion/Irritation Category 2  
Carcinogenicity Category 2  
Reproductive Toxicity Category 2  
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2  
Hazardous to the aquatic environment - Acute Category 2  
Flammable Liquid Category 3  
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3  
**GHS Signal Word:** Danger  
**GHS Hazard Statements:** Flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye damage.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.

# Safety Data Sheet

**Product Name:** Durabuild Gray

**Product identifier:** 102274

**Revision Date:** 09-16-2015

**Replaces:**

---

May cause damage to organs through prolonged or repeated exposure.  
Toxic to aquatic life.

**GHS Precautionary Statements:**

**Safety Precautions:**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Avoid release to the environment.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Use personal protective equipment as required.

**First Aid Measures:**

IF ON SKIN: Wash with plenty of soap and water.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.  
Rinse skin with water/shower.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Immediately call a POISON CENTER/doctor/....  
Call a POISON CENTER or doctor/physician if you feel unwell.  
Get medical advice/attention if you feel unwell.  
Specific treatment (see on this label).  
If skin irritation occurs: Get medical advice/attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use for extinction.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

**Disposal:**

Dispose of contents/container in accordance with  
local/regional/national/international regulation for hazardous wastes.

**Hazards not otherwise  
classified:**

No data available

# Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 09-16-2015

Replaces:

## 3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Toluene	108-88-3	10 - 30
n-Butyl acetate	123-86-4	7 - 15
2-Propanol	67-63-0	1 - 5
Titanium dioxide	13463-67-7	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First-aid measures

<b>Eye Contact:</b>	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel.
<b>Skin Contact:</b>	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
<b>Inhalation:</b>	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately
<b>Ingestion:</b>	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.
<b>Immediate medical attention and special treatment needed,:</b>	No additional first aid information available

## 5. Fire-fighting measures

<b>Suitable extinguishing media:</b>	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.
<b>Unsuitable extinguishing media:</b>	No data available
<b>Fire and/or Explosion Hazards:</b>	Vapors may be ignited by heat, sparks, flames or other sources of

# Safety Data Sheet

**Product Name:** Durabuild Gray

**Product identifier:** 102274

**Revision Date:** 09-16-2015

**Replaces:**

## **Hazardous Combustion**

### **Products:**

### **Special protective equipment and precautions for fire-fighters:**

ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Carbon dioxide, Carbon monoxide

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use methods for the surrounding fire.

## **6. Accidental release measures**

### **Personal precautions, protective equipment and emergency procedures:**

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

### **Methods and material for containment and cleaning up:**

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

## **7. Handling and storage**

### **Precautions for safe handling:**

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment

### **Conditions for safe storage:**

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

### **Materials to Avoid/Chemical Incompatibility::**

Strong oxidizing agents Strong alkalies Strong acids Metals

# Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 09-16-2015

Replaces:

## 8. Exposure controls/personal protection

### Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Toluene	100 ppm	100 ppm	
n-Butyl acetate	150 ppm	150 ppm	200 ppm STEL; 950 mg/m3 STEL
Titanium dioxide	15 mg/m3	10 mg/m3	

### Appropriate engineering controls.:

No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

### Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Wear goggles if dusts can reach the exposure limit.

### Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work

### Respiratory Protection:

Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Respiratory protection may be required in addition to ventilation depending upon conditions of use. NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter. Air purifying respirators should not be used in oxygen deficient or IDLH atmospheres

### Other Protective Equipment:

Wear goggles if dusts can reach the exposure limit.

### General Hygiene Conditions:

Use spark-proof tools and explosion-proof equipment

# Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 09-16-2015

Replaces:

## 9. Physical and chemical properties

Appearance (physical state):	Liquid
Color:	Grey
Odor:	Strong
Odor threshold:	No data available
pH:	7
Melting Point/Freezing Point (°C):	No data available
Initial Boiling Point and Boiling Range (°C):	111
Flash Point (°C):	4.4 26
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper Flammable/Explosive Limit:	7.6
Lower Flammable/Explosive Limit:	1
Vapor Pressure:	21 MMHG@20C/68F 8 MMHG@20C/68F
Vapor Density:	No data available
Relative Density:	1.26
Solubility(ies):	Insoluble
Partition coefficient: n-octanol/water:	1.36
Auto-ignition Temperature (°C):	420 °C
Decomposition Temperature::	No data available
Viscosity:	1200
VOC (as packaged-less exempts and water)	4.46 or
VOC (as applied*- 2% by wt hardener- less exempts and water)	4.27 or

## 10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Conditions to avoid:	None known. Contamination.
Incompatible materials:	Strong oxidizing agents Strong alkalies Strong acids Metals

## 11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact):	Inhalation, Skin contact, Eye contact, Absorption, Ingestion, Skin contact, Eye contact
--	---

### Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Can cause mechanical irritation if dusts are generated.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs)
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

# Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 09-16-2015

Replaces:

<b>Skin Absorption:</b>	permanent damage. Harmful if absorbed through the skin. May cause severe irritation and systemic damage.
<b>Eye Contact:</b>	Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible. Can cause mechanical irritation if dusts are generated.
<b>Ingestion Irritation:</b>	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
<b>Ingestion Toxicity:</b>	Harmful if swallowed. May cause systemic poisoning.

## Long-Term (Chronic) Health Effects:

<b>Carcinogenicity:</b>	Suspected of causing cancer.
<b>Reproductive and Developmental Toxicity:</b>	Suspected of damaging fertility or the unborn child.
<b>Mutagenicity:</b>	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
<b>Inhalation:</b>	Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")
<b>Skin Contact:</b>	Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
<b>Skin Absorption:</b>	Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

## Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
No data available			

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Titanium dioxide	N	Y	N

## 12. Ecological information

<b>Ecotoxicity (aquatic and terrestrial, where available):</b>	Toxic to aquatic life. Harmful to aquatic life. Components of this product are hazardous to wildlife and aquatic life.
<b>Persistence and degradability:</b>	No data available
<b>Mobility in soil:</b>	No data available
<b>Other adverse effects (such as</b>	No data available

# Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 09-16-2015

Replaces:

hazardous to the ozone layer):

## Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

## 13. Disposal considerations

**Description of waste residues:** Spent or discarded material is a hazardous waste.  
**Waste treatment methods**  
**(including packaging):** Dispose of by incineration following Federal, State, Local, or  
**Waste Disposal Code(s):** Provincial regulations.  
D001

## 14. Transport information

**UN proper shipping name:** The DOT Classification for shipping is dependent on quantity,  
type of packaging (a kit may include other components), or  
method of shipment.

## 15. Regulatory information

**TSCA Status:** All components in this product are on the TSCA Inventory.

## Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Toluene	108-88-3	N	N	Y	Y
Titanium dioxide	13463-67-7	N	N	Y	Y

## 16. Other information, including date of preparation or last revision.

**Revision Date:** 09-16-2015  
**Revision Number:** 8

**Disclaimer:** NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances