

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: IPII04

Product Name: ICE VIOLET
Product Use: None specified.
Print date: 24/Feb/2014

Revision Date: 28/Feb/2013

Company Identification
The Valspar Corporation

PO Box 1461

Minneapolis, MN 55440

Manufacturer's Phone: 1-612-851-7000

24-Hour Medical Emergency

24-110di Medicai Eillergency

Phone:

1-888-345-5732

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation Ingestion Skin absorption

Eye Contact:

· May cause eye irritation.

Skin Contact:

· Causes mild skin irritation.

Ingestion:

None known.

Inhalation:

- May cause irritation of respiratory tract.
- Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

	Approx. Weight %	Chemical Name
PROPRIETARY INERT	90 - 95	PROPRIETARY INERT
TITANIUM DIOXIDE 1317-80-2	5 - 10	Titanium dioxide
PROPRIETARY COLOR PIGMENT	.1 - 1	PROPRIETARY COLOR PIGMENT

If this section is blank there are no hazardous components per OSHA guidelines.

4. FIRST AID MEASURES

Eye Contact:

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water.

Skin Contact:

Wash off with plenty of water.

Ingestion:

Get medical attention if symptoms occur

Inhalation:

Move injured person into fresh air and keep person calm under observation. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Get medical attention immediately.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit): 401 Flash point (Celsius): 205

Lower explosive limit (%):

Upper explosive limit (%):

Autoignition temperature:

not determined
not determined

Sensitivity to impact:

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

Hazardous combustion products: See Section 10.

Unusual fire and explosion hazards:

None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Avoid contact with eyes.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep container closed when not in use.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Wear safety glasses or goggles to protect against exposure.

Skin protection:

Appropriate chemical resistant gloves should be worn.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

Ingredient Name	Approx.	TWA (final)	Ceilings limits (final)	Skin designations
CAS-No.	Weight %			
PROPRIETARY INERT	90 - 95	5 mg/m³ Respirable		
		fraction.		
		15 mg/m ³ Total dust		
TITANIUM DIOXIDE	5 - 10	15 mg/m ³ TWA dust		
1317-80-2		total		
PROPRIETARY COLOR	.1 - 1	2 mg/m3 TWA Sn excep	t	
PIGMENT		oxides		

ACGIH Threshold Limit Value (TLV's)

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
PROPRIETARY INERT	90 - 95	1 fiber/cm3 TWA			
		respirable fibers:			
		length >5 μm,			
		aspect ratio >=3:1,			
		as determined by			
		the membrane filter			
		method at 400-450X			
		magnification [4-mm			
		objective], using			
		phase-contrast			
		illumination			
		Synthetic vitreous			
		fibers			
		5 mg/m ³ TWA			
		inhalable fraction			
		Synthetic vitreous			
		fibers			
PROPRIETARY COLOR	.1 - 1	2 mg/m ³ TWA			
PIGMENT		except Tin hydride			
		Sn			

9. PHYSICAL PROPERTIES

Odor: Normal for this product type.

Physical State: powder

pH: not determined

Vapor pressure: not determined mmHg @ 68°F (20°C)

Boiling point: 4532°F (2500°C)
Solubility in water: not determined
Coefficient of water/oil distribution: not determined

Density (lbs per US gallon): 21.32 Specific Gravity: 2.559

Evaporation rate (butyl acetate = 1.0): not determined

Flash point (Fahrenheit): 401
Flash point (Celsius): 205

Lower explosive limit (%):

Upper explosive limit (%):

Autoignition temperature:

not determined
not determined

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: None known.

Incompatibility: Strong oxidizing agents Acids

Hazardous Polymerization: None anticipated.

Hazardous Decomposition Products: Silicon dioxide. Carbon monoxide and carbon dioxide.

Metal oxide fumes.

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

11. TOXICOLOGICAL INFORMATION

11. TOXICOLOGICAL INFORMATION

	Approx. Weight %	NIOSH - Selected LD50s and LC50s
TITANIUM DIOXIDE 1317-80-2	5 - 10	> 10000 mg/kg Oral LD50 Rat
PROPRIETARY COLOR PIGMENT	.1 - 1	> 20 g/kg Oral LD50 Rat

Mutagens/Teratogens/Carcinogens:

Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
TITANIUM DIOXIDE	5 - 10			Monograph 47 [1989]
1317-80-2				

•	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
TITANIUM DIOXIDE 1317-80-2	5 - 10	Present		

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

Proper Shipping Name: PIGMENT, NOT REGULATED

U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

Reportable Quantity Description:

International Air Transport Association (IATA):

Proper shipping name: NOT REGULATED

International Maritime Organization (IMO):

Proper shipping name: NOT REGULATED

Marine Pollutant No

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

15. REGULATORY INFORMATION

SARA 311/312 Hazard Class:

Acute: yes
Chronic: no
Flammability: no
Reactivity: no
Sudden Pressure: no

U.S. STATE REGULATIONS:

Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317

Pennsylvania Right To Know:

PROPRIETARY COLOR PIGMENT Trade Secret

TITANIUM DIOXIDE 1317-80-2
PROPRIETARY INERT Trade Secret

Rule 66 status of product

Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

16. OTHER INFORMATION

HMIS Codes

Health: 1 Flammability: 0 Reactivity: 0

PPE: X - See Section 8 for Personal Protective Equipment (PPE).

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Regulatory Affairs Department 24/Feb/2014 28/Feb/2013

Preparation Information:
Prepared By:
Print date: Revision Date: