



# AIRCRAFT® ULTRA™ Paint Remover

Technical Data Sheet – For Use in Non-VOC Regulated States\*

**GAR4000, QAR4000**  
**EAR4000**

Gallon, Quart Liquid  
15 oz Aerosol



*New AIRCRAFT® ULTRA™ brings back power and speed!*

- Strips to bare metal in 30 minutes or less†
- Designed specifically to remove 2K/OEM automotive coatings
- For use on metal, fiberglass, flexible & rigid plastics
- \*Not for sale in CA, CO, CT, DE, MD, MI, NH, NY, OH, RI and UT (Continue using GAR2000, QAR2000 and EAR2000 in these states.)

## DIRECTIONS FOR USE

Carefully read the entire product label and precautions on the SDS prior to use. Protect hands with solvent-resistant gloves and eyes with chemical splash goggles.

1. Mask seams and trim openings. This will prevent bleed-back stripping of new finish.
2. Sand the surface prior to application with 80 to 180 grit.
3. Shake Well.
4. Liquid: Pour on a thick coat and use a chemical-resistant spreader to move over the surface. Do not brush on thinly.

Aerosol: Hold can in an upright position and point arrow on top of button away from you. Spray at a distance of approximately 8” to 12” from surface. To avoid sagging on vertical surfaces, use a back-and-forth motion to apply a generous, even coat.

Apply to one section at a time, up to 3 ft. x 3 ft.

**Note: Always apply a generous amount of remover. Thin coats can dry too quickly for the remover to work effectively. Do not apply with a paint brush.**



5. Allow remover to work until finish is blistered or softened completely, generally within 30 minutes. Some coatings may require up to 2 hours. If the coating has not begun to lift after 30 minutes, reapply another layer of remover.  
**Note: To speed up removal time, and to minimize evaporation, place plastic sheeting over wet remover.**
6. If applied to a plastic surface, check every 10 minutes. Remover left on some types of plastic for an extended period of time can cause damage.
7. Remove paint with a flexible plastic scraper, then rinse with water or mineral spirits to remove any residue. Prime metal as soon as possible to prevent flash rust. Allow plastic and fiberglass to dry 12 hours.

**NOTE:** This product may not be compatible with all surfaces and all conditions surrounding application. Before applying to any surface, always test product in a small, inconspicuous area to ensure no damage will result. Not recommended for use on synthetic surfaces. For best results, apply at temperatures between 65°F and 85°F, and avoid direct sunlight. Repeated applications of this product in an attempt to remove the OEM finish from plastic can cause swelling and distortion of the part. Some older bumpers may swell during application but will return to the original contour within 24 hours. Do not apply new finish until swelling has gone down.

**DO NOT USE TO STRIP BATHTUBS  
NOT INTENDED FOR USE ON AIRCRAFT**

†Works on most coatings in less than 30 minutes. Times may vary based on coating type and temperature.

**ORDERING INFORMATION**

Product	Size	Pack	Unit Wt.	Width	Depth	Height	UPC Code	Pallet Qty
QAR4000	QT	6	2.83	4.56"	2.37"	7.50"	0-30192-14000-0	750 units
GAR4000	GL	4	5.48	6.62"	4.12"	10.31"	0-30192-04000-3	208 units
EAR4000	15oz	12	1.50	2.69"	2.69"	9.69"	0-30192-24000-7	1020





## AIRCRAFT® ULTRA™ Paint Remover

	<b>GAR4000/QAR4000</b>
<b>Appearance</b>	Thick white to slightly yellow or reddish opaque gel
<b>Percent Volatile</b>	95.9%
<b>Flash Point</b>	6°F
<b>CPSC Flammability Classification</b>	Extremely Flammable
<b>VOC Category/Limit</b>	Paint Remover, 50% by weight
<b>Actual VOC</b>	Liquid: 80.5% by weight (709 g/L)
<b>Storage</b>	Store in a cool place. Prolonged exposure to temps in excess of 90°F may cause can to leak or swell. Do not reuse container. Once opened, remover should be used within 6 months or disposed of properly to avoid can deterioration.
<b>Density</b>	7.36 lbs/gal
<b>Shelf Life</b>	2 years from date of manufacture, in an unopened container
<b>DOT</b>	UN3469, PAINT RELATED MATERIAL FLAMMABLE, CORROSIVE, 3 (8), PGII (quart ships as Ltd Qty)
<b>PROP 65</b>	 <b>WARNING:</b> This product can expose you to chemicals including Cumene and Ethylbenzene, which are known to the State of California to cause cancer, and Methanol, which is known to the state of California to cause birth defects and other reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> .
<b>Restrictions</b>	CA, CO, CT, DE, MD, MI, NH, NY, OH, RI and UT

	<b>EAR4000</b>
<b>Appearance</b>	Tan viscous gel
<b>Percent Volatile</b>	95.9%
<b>Flash Point of the Concentrate</b>	6°F
<b>CPSC Flammability Classification</b>	Extremely Flammable
<b>VOC Category/Limit</b>	Paint Remover, 50% by weight
<b>Actual VOC</b>	85% by weight (758.6 g/L)
<b>Storage</b>	Replace overcap after use. Contents under pressure. Do not puncture, incinerate or store above 120°F. Exposure to heat or prolonged exposure to sun can cause bursting.
<b>Density</b>	7.45 lbs/gal
<b>Shelf Life</b>	2 years from date of manufacture, in an unopened container
<b>DOT</b>	UN1950, AEROSOLS, flammable, corrosive, 2.1 (8), LTD QTY)
<b>PROP 65</b>	 <b>WARNING:</b> This product can expose you to chemicals including Cumene and Ethylbenzene, which are known to the State of California to cause cancer, and Methanol, which is known to the state of California to cause birth defects and other reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> .
<b>Restrictions</b>	CA, CO, CT, DE, MD, MI, NH, NY, OH, RI and UT

