

MATERIAL SAFETY DATA SHEET**844-0982 CHROMA-CHEM®LEAD FREE ORANGE****UO**

Material no.		Version	4.0 / US
Specification	139811	Revision date	04/09/2011
Order Number		Print Date	04/06/2013
		Page	1 / 8

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product information**

Trade name : 844-0982 CHROMA-CHEM®LEAD FREE ORANGE UO
Use of the Substance / : Non-aqueous colorant
Preparation
Company : Chromaflo Technologies Corporation
2600 Michigan Avenue
Ashtabula, OH 44005-0816
USA

Telephone : 440-997-5137

Telefax : 440-992-3613

US: CHEMTREC EMERGENCY : 800-424-9300
NUMBER

CANADA: CANUTEC : 613-996-6666
EMERGENCY NUMBER

Product Regulatory Services : 440-536-9691

2. HAZARDS IDENTIFICATION***** EMERGENCY OVERVIEW *****

Form-paste **Color**-orange **Odor**-Sweet ether-like odor.

May cause eye, skin and respiratory tract irritation.
Combustible liquid and vapor.

POTENTIAL HEALTH EFFECTS**Eye contact**

May cause eye irritation.

Skin Contact

May cause skin irritation.
Prolonged skin contact with large amounts of ether acetates may cause drowsiness.

Inhalation

Possibly irritating.
Excessive inhalation of solvent vapors may cause nasal and respiratory irritation and central nervous system effects including dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even death.

Ingestion

MATERIAL SAFETY DATA SHEET**844-0982 CHROMA-CHEM®LEAD FREE ORANGE****UO**

Material no.

Version

4.0 / US

Specification

139811

Revision date

04/09/2011

Order Number

Print Date

04/06/2013

Page

2 / 8

May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Chronic Health Hazard

High vapor concentrations (3000 ppm) of propylene glycol monomethyl ether acetate caused upper respiratory irritation and liver and kidney effects in subchronic animal testing. The relevance of these results to humans is not known.

Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Information on ingredients / Hazardous components**

2-methoxy-1-methylethyl acetate

CAS-No.

108-65-6

Percent (Wt./ Wt.)

10 - 30 %

Stoddard solvent; Low boiling point naphtha - unspecified

CAS-No.

8052-41-3

Percent (Wt./ Wt.)

10 - 30 %

Distillates (petroleum), hydrodesulfurized middle; Gasoil - unspecified

CAS-No.

64742-80-9

Percent (Wt./ Wt.)

1 - 5 %

Polymeric Amide

CAS-No.

Percent (Wt./ Wt.)

1 - 5 %

Other information

This material is classified as hazardous under OSHA regulations.

4. FIRST AID MEASURES**Inhalation**

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If unconscious, evaluate the need for artificial respiration. Get immediate medical attention.

Skin contact

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Thoroughly wash clothing, shoes and protective equipment before reuse or discard. Get medical attention if irritation develops or persists.

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes or until all material has been removed. Obtain medical attention.

Ingestion

Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

Never administer anything by mouth to an individual who rapidly losing consciousness, unconscious or convulsing.

If the heart has stopped or breathing has stopped, trained personnel should begin cardiopulmonary resuscitation or artificial respiration immediately.

MATERIAL SAFETY DATA SHEET

844-0982 CHROMA-CHEM®LEAD FREE ORANGE

UO



Material no.		Version	4.0 / US
Specification	139811	Revision date	04/09/2011
Order Number		Print Date	04/06/2013
		Page	3 / 8

5. FIRE-FIGHTING MEASURES

Flash point 42.22 °C , 108 °F
Method: Setaflash Closed Cup

OSHA Flammability Classification Combustible Liquid

Suitable extinguishing media

Use water spray or fog, foam, dry chemical or CO2.

Specific hazards during fire fighting

Combustible liquid. Vapors can travel to a source of ignition and flash back. Explosive mixtures may occur at temperatures at or above the flashpoint.

Further information

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear. Containers can build up pressure if exposed to heat (fire). Cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Additional advice

Absorb spill with inert material, then place in a chemical waste container. After removal, flush contaminated area with water and collect for disposal. Clean up spills immediately. Remove sources of ignition and ventilate area. Use a respirator and other protective equipment as outlined in Section 8. Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

7. HANDLING AND STORAGE

Handling

Safe handling advice

Keep away from heat. Keep away from sparks, flames and other sources of ignition. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use with adequate ventilation. The need for grounding and bonding of containers in accordance with OSHA 29 CFR 1910.106 and NFPA 77 should be assessed for all product transfers. Follow all MSDS/label precautions even after the container is emptied because it may retain product residues. Wash thoroughly after handling.

Storage

Requirements for storage areas and containers

Keep in a dry, cool place.

Keep container closed when not in use.

Residual vapors might explode on ignition; do not apply heat, cut, drill, grind or weld on or near this container.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component occupational exposure guidelines

MATERIAL SAFETY DATA SHEET**844-0982 CHROMA-CHEM®LEAD FREE ORANGE****UO**

Material no.

Version

4.0 / US

Specification

139811

Revision date

04/09/2011

Order Number

Print Date

04/06/2013

Page

4 / 8

- **Stoddard solvent; Low boiling point naphtha - unspecified**

CAS-No. 8052-41-3

Control parameters 100 ppm

500 ppm

2900 mg/m3

100 ppm

525 mg/m3

Time Weighted Average (TWA):(ACGIH)

PEL:(OSHA Z1)

Time Weighted Average (TWA)

Permissible Exposure Limit (PEL):(US CA
OEL)**Other information**

Exposure values for mineral spirits (CAS Nr 8052-41-3) are given as Stoddard solvent.

The AIHA WEEL for propylene glycol monomethyl ether acetate is 50 ppm TWA.

Engineering measures

Use explosion-proof ventilation equipment.

Personal protective equipment**Respiratory protection**

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

Hand protection

Use impermeable gloves.

Personal protective equipment that provides a barrier to prevent dermal exposure to this substance is required.

Eye protection

Chemical resistant goggles must be worn.

Skin and body protection

A safety shower and eye wash fountain should be readily available.

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance**

Form

paste

Color

orange

Odor

Sweet ether-like odor.

Safety data

Boiling point/range

> 143 °C

Flash point

42.22 °C

Method: Setaflash Closed Cup

Relative density

1

MATERIAL SAFETY DATA SHEET**844-0982 CHROMA-CHEM®LEAD FREE ORANGE****UO**

Material no.

Version

4.0 / US

Specification

139811

Revision date

04/09/2011

Order Number

Print Date

04/06/2013

Page

5 / 8

Solubility/qualitative

Solubility in water: Negligible.

Viscosity, dynamic

52 - 62 KU (25 °C)

Solvents and Volatiles Data

% VOC (gm/l)

516

Evaporation rate

Slower than butyl acetate

10. STABILITY AND REACTIVITY

Conditions to avoid

Avoid high temperatures and sources of ignition.

Materials to avoid

oxidizing substances

11. TOXICOLOGICAL INFORMATION

Component Acute oral toxicity

2-methoxy-1-methylethyl acetate

108-65-6

LD50 Rat: 8532 mg/kg

Stoddard solvent; Low boiling point naphtha - unspecified

8052-41-3

LD50 Rat: > 5000 mg/kg

Distillates (petroleum), hydrodesulfurized middle; Gasoil - unspecified

64742-80-9

LD50 Rat: > 5000 mg/kg

Component Acute inhalation toxicity

LC50 (rat) > 4345 ppm, 6 hours, vapor

related to substance: 2-methoxy-1-methylethyl acetate

Stoddard solvent; Low boiling point naphtha - unspecified

8052-41-3

LC50 Rat: > 5500 mg/m3 / 4 h

Distillates (petroleum), hydrodesulfurized middle; Gasoil - unspecified

64742-80-9

LC50 Rat: 4600 mg/m3 / 4 h

Component Acute dermal toxicity

2-methoxy-1-methylethyl acetate

108-65-6

LD50 Rabbit: > 19000 mg/kg

(calculated)

(literature value)

Stoddard solvent; Low boiling point naphtha - unspecified

8052-41-3

LD50 Rabbit: > 3000 mg/kg

Distillates (petroleum), hydrodesulfurized middle; Gasoil - unspecified

MATERIAL SAFETY DATA SHEET**844-0982 CHROMA-CHEM®LEAD FREE ORANGE****UO**

Material no.

Version

4.0 / US

Specification

139811

Revision date

04/09/2011

Order Number

Print Date

04/06/2013

Page

6 / 8Component General Toxicity
Information

64742-80-9

LD50 Rabbit: > 2000 mg/kg

2-methoxy-1-methylethyl acetate
108-65-6

High vapor concentrations (3000 ppm) of propylene glycol monomethyl ether acetate caused upper respiratory irritation and liver and kidney effects in subchronic animal testing. The relevance of these results to humans is not known.

12. ECOLOGICAL INFORMATION

General Ecological Information

No ecotoxicological studies are available.

13. DISPOSAL CONSIDERATIONS**WASTE DISPOSAL**

Advice on disposal

Waste must be disposed of in accordance with federal, state, provincial and local regulations. **CONTAINER DISPOSAL:** Empty containers by removing the top and inverting to allow all free-flowing product to drain. To meet regulatory criteria, the container is considered empty when less than 3% remains in the container. Additional special handling is not typically required and the empty container can be discarded with other non-hazardous trash. Note: Local disposal regulations may be more stringent and require additional restrictions or precautions. Customers should check with their local disposal company, municipal or state authority. Recycle of plastic or metal containers may require clean rather than empty containers. In this case the containers can be rinsed with mineral spirits until the containers are considered generally product free.

14. TRANSPORT INFORMATION**Sea transport IMDG-Code**

Class

3

UN-No

1263

Packaging group

III

EmS

F-E, S-E

Proper technical name (Proper shipping name)

PAINT RELATED MATERIAL**Air transport ICAO-TI/IATA-DGR**

Class

3

UN-No

1263

Packaging group

III

Proper technical name (Proper shipping name)

Paint related material

MATERIAL SAFETY DATA SHEET**844-0982 CHROMA-CHEM®LEAD FREE ORANGE****UO**

Material no.

Version

4.0 / US

Specification

139811

Revision date

04/09/2011

Order Number

Print Date

04/06/2013

Page

7 / 8**Loading instructions/Remarks**

IATA_C ERG-Code 3L

IATA_P ERG-Code 3L

CFR_INWTR In the U.S. this material may be classified as combustible liquid.
Combustible liquids are not regulated in packages 450 liters or less.
This applies for shipments by road and rail only.

CFR_RAIL In the U.S. this material may be classified as combustible liquid.
Combustible liquids are not regulated in packages 450 liters or less.
This applies for shipments by road and rail only.

CFR_ROAD In the U.S. this material may be classified as combustible liquid.
Combustible liquids are not regulated in packages 450 liters or less.
This applies for shipments by road and rail only.

15. REGULATORY INFORMATION**US Federal Regulations****OSHA**

If listed below, chemical specific standards apply to the product or components:

- None listed

Clean Air Act Section (112)

If listed below, components present at or above the de minimus level are hazardous air pollutants:

- None listed

CERCLA Reportable Quantities

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

- None listed

SARA Title III Section 311/312 Hazard Categories

The product meets the criteria only for the listed hazard classes:

- Acute Health Hazard
- Chronic Health Hazard
- Fire Hazard

SARA Title III Section 313 Reportable Substances

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- None listed

Toxic Substances Control Act (TSCA)

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

MATERIAL SAFETY DATA SHEET**844-0982 CHROMA-CHEM®LEAD FREE ORANGE****UO**

Material no.

Version

4.0 / US

Specification

139811

Revision date

04/09/2011

Order Number

Print Date

04/06/2013

Page

8 / 8

- None listed

State Regulations**California Proposition 65**

A warning under the California Drinking Water Act is required only if listed below:

- None listed

International Chemical Inventory Status

Unless otherwise noted, this product is in compliance with the inventory listing of the countries shown below. For information on listing for countries not shown, contact the Product Regulatory Services Department.

- | | |
|--------------------------|---------------------------|
| • Europe (EINECS/ELINCS) | Listed/registered |
| • USA (TSCA) | Listed/registered |
| • Canada (DSL) | Listed/registered |
| • Australia (AICS) | Not listed/Not registered |
| • Japan (MITI) | Not listed/Not registered |
| • Korea (TCCL) | Not listed/Not registered |
| • Philippines (PICCS) | Not listed/Not registered |
| • China | Listed/registered |
| • New Zealand | Listed/registered |

16. OTHER INFORMATION**HMIS Ratings**

Health :	2
Flammability :	2
Physical Hazard :	0

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.