

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 1/17

Printing date: 14.07.2014

Revision: 14.07.2014

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** High Temperature Flat Black - Aerosol
- **Article number:** 44218
- **1.2 Relevant identified uses of the substance or mixture and uses advised against:**
No further relevant information available.
- **Application of the substance / the mixture:** Coating material
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Absolute Coatings Inc.
38 Portman Road
New Rochelle, NY 10801
Phone: 1-800-221-8010
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H222-H229, H361d.
The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H222, H304, H361.



H222: Extremely flammable aerosol.



Repr. 2 H361: Suspected of damaging fertility or the unborn child.



H304: May be fatal if swallowed and enters airways.



Flame

Flam. Aerosol 1; H222-H229: Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

Muta. 1B; H340: May cause genetic defects.

Carc. 1B; H350: May cause cancer.

(Contd. on page 2)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 2/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 1)

Repr. 2; H361d: Suspected of damaging the unborn child.

STOT RE 2; H373: May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2; H315: Causes skin irritation.

Eye Irrit. 2; H319: Causes serious eye irritation.

STOT SE 3; H336: May cause drowsiness or dizziness.

Asp. Tox. 1; H304: May be fatal if swallowed and enters airways.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R48/20-63: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Possible risk of harm to the unborn child.



Xi; Irritant

R36/38: Irritating to eyes and skin.



F+; Extremely flammable

R12: Extremely flammable.

R67: Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

toluene

Solvent naphtha (petroleum), light aliph.

(Contd. on page 3)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 3/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 2)

· **Hazard statements**

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H222, H304, H361.

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H222-H229, H361d.

H222: Extremely flammable aerosol.

H361: Suspected of damaging fertility or the unborn child.

H304: May be fatal if swallowed and enters airways.

H222-H229: Extremely flammable aerosol. Pressurised container: May burst if heated.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H340: May cause genetic defects.

H350: May cause cancer.

H361d: suspected of damaging the unborn child.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251: Pressurized container: Do not pierce or burn, even after use.

P281: Use personal protective equipment as required.

P260: Do not breathe mist/vapours/spray.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· **Additional information:**

Restricted to professional users.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

· **Hazard description:**

· **WHMIS-symbols:**

B5 - Flammable aerosol

D2A - Very toxic material causing other toxic effects



· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



* - Indicates a long term health hazard from repeated or prolonged exposures.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 4/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 3)

· HMIS Long Term Health Hazard Substances

108-88-3|toluene

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.
























· **vPvB:** Not applicable.

3 Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3	toluene  Xn R48/20-63-65;  Xi R38;  F R11 R67 Repr. Cat. 3  Flam. Liq. 2, H225  Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone  Xi R36;  F R11 R66-67  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane  F+ R12  Flam. Gas 1, H220  Press. Gas, H280	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane  F+ R12  Flam. Gas 1, H220  Press. Gas, H280	10-25%
CAS: 64742-89-8 EINECS: 265-192-2 Index number: 649-267-00-0	Solvent naphtha (petroleum), light aliph.  Xn R65  Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	2,5-10%
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	2,5-10%
	xylene  Xn R20/21;  Xi R38;  F R11  Flam. Liq. 2, H225  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	□ 2,5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

(Contd. on page 5)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 5/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 4)

4 First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

In cases of frost bites, rinse with plenty of water. Do not remove clothing.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

· **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Irritant to skin and mucous membranes.

Irritant to eyes.

Breathing difficulty

Coughing

Frost bites

Nausea

Cramp

Disorientation

· **Hazards**

Danger of pulmonary oedema.

Danger of pneumonia.

Danger of convulsion.

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Contains toluene. Consult literature for specific antidotes.

If swallowed, gastric irrigation with added, activated carbon. May produce a hypnotic/narcotic effect.

Do not administer preparations of the adrenalin-ephedrine-group.

If swallowed or in case of vomiting, danger of entering the lungs.

Monitor circulation, possible shock treatment.

Medical supervision for at least 48 hours.

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 6/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 5)

If necessary oxygen respiration treatment.
Later observation for pneumonia and pulmonary oedema.
Vapours may cause drowsiness and dizziness.

5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Danger of receptacles bursting because of high vapour pressure when heated.
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information**
Eliminate all ignition sources if safe to do so.
Use large quantities of foam as it is partially destroyed by the product.
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
Cool endangered receptacles with water fog or haze.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
Protect from heat.
Particular danger of slipping on leaked/spilled product.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Allow to evaporate.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Pick up mechanically.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 7/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 6)

7 Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.
Keep away from heat and direct sunlight.
Take note of emission threshold.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
Emergency cooling must be available in case of nearby fire.
Fumes can combine with air to form an explosive mixture.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
Provide ventilation for receptacles.
Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.
Store away from oxidizing agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles. Keep container tightly sealed.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

· 7.3 Specific end use(s): No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

PEL (USA)	Long-term value: 200 ppm Ceiling limit: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm BEI

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 8/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 7)

EL (Canada)	Long-term value: 20 ppm R
EV (Canada)	Long-term value: 20 ppm
74-98-6 propane	
PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F: minimal oxygen content
EL (Canada)	Long-term value: 1000 ppm
EV (Canada)	Long-term value: 1,000 ppm
67-64-1 acetone	
IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm
PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-475 mg/m ³ , (500) NIC-200 ppm BEI
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm
EV (Canada)	Short-term value: 750 ppm Long-term value: 500 ppm
106-97-8 butane	
REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm
EL (Canada)	Short-term value: 750 ppm Long-term value: 600 ppm
EV (Canada)	Long-term value: 800 ppm
7727-43-7 barium sulphate, natural	
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: (10) NIC-5* mg/m ³ *inhalable fraction
EL (Canada)	Long-term value: 10 mg/m ³
EV (Canada)	Long-term value: 10 mg/m ³ total dust
xylene	
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 9/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 8)

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
EV (Canada)	Short-term value: 650 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

· **Ingredients with biological limit values:**

108-88-3 toluene

BEI (USA)	0,02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0,03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0,3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

67-64-1 acetone

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

xylenes

BEI (USA)	1,5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

- **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.

(Contd. on page 10)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 10/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 9)

Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Do not carry product impregnated cleaning cloths in trouser pockets.
Pregnant women should strictly avoid inhalation or skin contact.

• **Respiratory protection:**

Not required under normal conditions of use.
Use suitable respiratory protective device in case of insufficient ventilation.
Use suitable respiratory protective device when high concentrations are present. For spills, respiratory protection may be advisable.
NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Safety glasses

- **Body protection:** Solvent resistant protective clothing
- **Limitation and supervision of exposure into the environment**

No further relevant information available.

• **Risk management measures**

See Section 7 for additional information.
No further relevant information available.

9 Physical and chemical properties

• **9.1 Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:	Aerosol
Colour:	Black
Odour:	Aromatic

(Contd. on page 11)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 11/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 10)

- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**
 - Melting point/Melting range:** Not Determined.
 - Boiling point/Boiling range:** -47,2 ° F / -44 °C
- **Flash point:** -2,2 ° F / -19 °C
- **Flammability (solid, gaseous):** Not applicable.
- **Auto/Self-ignition temperature:** 689 ° F / 365 °C
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not self-igniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
 - Lower:** 1,5 Vol %
 - Upper:** 10,9 Vol %
- **Vapour pressure at 20 °C:** 2750 hPa
- **Density at 20 °C:** 0,77 - 0,85 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **9.2 Other information** No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**

Danger of receptacles bursting because of high vapour pressure when heated.
Avoid temperatures above 120 °F / 48,9 °C.
- **10.3 Possibility of hazardous reactions**

Develops readily flammable gases/fumes.
Flammable.
Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

(Contd. on page 12)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 12/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 11)

Danger of receptacles bursting because of high vapour pressure when heated.
Toxic fumes may be released if heated above the decomposition point.

· **10.4 Conditions to avoid**

Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
Keep away from heat and direct sunlight.

· **10.5 Incompatible materials:** No further relevant information available.

· **10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide
Hydrocarbons
Flammable gases/vapours
Irritant gases/vapours

11 Toxicological information

· **11.1 Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4h	5320 mg/l (mouse)

· **Primary irritant effect:**

· **On the skin:** Irritant to skin and mucous membranes.

· **In the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

Toxic and/or corrosive effects may be delayed up to 12 hours.

· **Acute effects (acute toxicity, irritation and corrosivity):**

Vapours have narcotic effect.

Danger through skin adsorption.

· **Repeated dose toxicity:** May cause damage to organs through prolonged or repeated exposure.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**

Muta. 1B, Carc. 1B, Repr. 2

12 Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:** The product contains materials that are harmful to the environment.

· **12.2 Persistence and degradability:** The product is partially biodegradable. Significant residuals remain.

(Contd. on page 13)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 13/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 12)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Avoid transfer into the environment.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects:** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 AEROSOLS, FLAMMABLE
- **IMDG, IATA** AEROSOLS, FLAMMABLE
- **14.3 Transport hazard class(es)**

- **DOT**



- **Class** 2.1
- **Label** 2.1

- **ADR**



- **Class** 2.1 5F
- **Label** 2.1

(Contd. on page 14)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 14/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 13)

· **IMDG, IATA**



· Class	2.1
· Label	2.1
· 14.4 Packing group	
· DOT, ADR, IMDG, IATA	Not Regulated
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	D
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
----------	---------

	xylenes
--	---------

· **TSCA (Toxic Substances Control Act):**
All ingredients are listed.

· **Proposition 65 (California):**

· **Chemicals known to cause cancer:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

(Contd. on page 15)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 15/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 14)

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

108-88-3 toluene

II

67-64-1 acetone

I

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

xylenes

I

· **IARC (International Agency for Research on Cancer)**

108-88-3 toluene

3

xylenes

3

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3 toluene

A4

67-64-1 acetone

A4

xylenes

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**
All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**
None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

108-88-3 toluene

67-64-1 acetone

106-97-8 butane

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.
HSNO Numbers: 2.1.2A, 6.6A, 6.7A, 6.1E, 6.8B, 6.9B, 6.3A, 6.4A

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 16)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 16/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 15)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
.....
R11 Highly flammable.
R12 Extremely flammable.
R20/21 Harmful by inhalation and in contact with skin.
R36 Irritating to eyes.
R38 Irritating to skin.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Gas 1: Flammable gases, Hazard Category 1
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas: Gases under pressure: Compressed gas
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

(Contd. on page 17)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Page 17/17

Printing date: 14.07.2014

Revision: 14.07.2014

Trade name: High Temperature Flat Black - Aerosol

(Contd. of page 16)

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Muta. 1B: Germ cell mutagenicity, Hazard Category 1B
Carc. 1B: Carcinogenicity, Hazard Category 1B
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1