



TECH DATA SHEET

CUTTING COMPOUND (1314)

DESCRIPTION

Presta® Cutting Compound cuts quickly and is designed to remove P1200 and finer sand scratches on most new and aged clear coat paint surfaces over a broad range of buffing speeds. Contains no waxes, fillers or silicones making it 100% body shop safe. This water-based formula is easy-to-use and significantly reduces buffing and cleanup time when used in conjunction with Presta Finishing Polish.

DIRECTIONS

Shake well before using. Surface should be clean, cool and dry. For best results, use with a Presta 100% twisted white wool cutting pad. Apply a 2" dab of Cutting compound for a 2' x 2' section and spread with the pad before initiating rotation. Buff at speed between 1600 - 2200 rpm. Work the buffer slowly from side to side and front to rear until most of the product is gone and gloss appears. Repeat as necessary for deeper scratches or heavier oxidation. Remove any remaining compound with a damp cloth. For optimal results on dark finishes, follow with Finishing Polish (#1323).

COMPOUND PART NUMBERS

Compound Size	Compound Part #	Case Qty.
32 oz. Cutting Compound	131432	12
1 gal. Cutting Compound	131401	4

FEATURES AND BENEFITS

Aggressive enough to remove severe scratches	<ul style="list-style-type: none">• Compound has a long working window that can handle P1200 sand scratches
Water-based formula	<ul style="list-style-type: none">• Significantly reduces cleanup time
Low dusting formula	<ul style="list-style-type: none">• Keeps the rest of the vehicle clean while you work• Allows for faster clean up
Contains no waxes, fillers or silicones	<ul style="list-style-type: none">• 100% body shop safe• Mechanical correction, scratches will not reappear with washing or time