

1 Identification

· **Product identifier**

· **Trade name:** 15003-15893 Color Coat Aerosol

· **Article number:**

15003, 15013, 15023, 15033, 15043, 15053, 15063, 15083, 15093, 15103, 15113, 15123, 15133, 15143, 15163, 15173, 15183, 15213, 15223, 15233, 15243, 15253, 15273, 15283, 15293, 15303, 15313, 15323, 15353, 15363, 15373, 15393, 15413, 15423, 15433, 15453, 15463, 15473, 15483, 15493, 15603, 15643, 15673, 15703, 15713, 15723, 15753, 15763, 15773, 15783, 15793, 15803, 15813, 15823, 15833, 15843, 15853, 15863, 15873, 15883, 15893

· **Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture** Coating

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225

· **Information department:**

cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Carc. 2	H351	Suspected of causing cancer.
Repr. 2	H361	Suspected of damaging fertility or the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)


Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 1)

· Hazard pictograms


GHS02 GHS04 GHS07 GHS08

· Signal word *Danger*
· Hazard-determining components of labeling:

 toluene
 acetone
 4-methylpentan-2-one
 butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 1

Fire = 4

Reactivity = 3

· HMIS-ratings (scale 0 - 4)


Health = *1

Fire = 4

Reactivity = 3

· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

(Contd. on page 3)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization:** Mixtures

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

67-64-1	acetone	30 - 40%
68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
108-88-3	toluene	10 - 13%
110-19-0	isobutyl acetate	1.5 - 5%
108-10-1	4-methylpentan-2-one	1.5 - 5%
78-93-3	butanone	1.5 - 5%
108-65-6	2-methoxy-1-methylethyl acetate	1-1.5%
2807-30-9	2-(propyloxy)ethanol	1-1.5%
13463-67-7	titanium dioxide	≤1%
1333-86-4	Carbon black	≤1%
67-56-1	methanol	≤1%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

USA

(Contd. on page 4)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not gas tight seal receptacle.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
-----	--

(Contd. on page 5)



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 4)

REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI
108-88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI
110-19-0 isobutyl acetate	
PEL	Long-term value: 700 mg/m ³ , 150 ppm
REL	Long-term value: 700 mg/m ³ , 150 ppm
TLV	Long-term value: 713 mg/m ³ , 150 ppm
108-10-1 4-methylpentan-2-one	
PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI
78-93-3 butanone	
PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI
108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm
67-56-1 methanol	
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI
· Ingredients with biological limit values:	
67-64-1 acetone	

(Contd. on page 6)


Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 5)

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
108-88-3 toluene	
BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
108-10-1 4-methylpentan-2-one	
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
78-93-3 butanone	
BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK
67-56-1 methanol	
BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 7)

USA

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 6)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C

· **Flash point:** -103 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 465 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:	1.2 Vol %
Upper:	13.0 Vol %

· **Vapor pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 0.81036 g/cm³

· **Relative density** Not determined.

(Contd. on page 8)


Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 7)

- | | |
|---|--|
| · Vapour density | Not determined. |
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 90.1 % |
| VOC content: | 54.8 % |
| | 696.1 g/l / 5.81 lb/gl |
| · Solids content: | 10.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

108-88-3 toluene

3

(Contd. on page 9)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 8)

108-10-1	4-methylpentan-2-one	2B
13463-67-7	titanium dioxide	2B
1333-86-4	Carbon black	2B
7631-86-9	silicon dioxide, chemically prepared	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS

(Contd. on page 10)

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 9)

· **IATA** AEROSOLS, flammable

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1

· **Label** 2.1

· **ADR**



· **Class** 2 5F Gases

· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1

· **Label** 2.1

· **Packing group**

· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user** Warning: Gases

· **EMS Number:** F-D,S-U

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **Hazardous substance:** 1 lbs, 0.454 kg

· **ADR**

· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

(Contd. on page 11)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 10)

· **UN "Model Regulation":** UN1950, Aerosols, 2.1

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
	ACRYLIC RESIN
108-10-1	4-methylpentan-2-one
78-93-3	butanone
67-56-1	methanol
1330-20-7	xylene
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone
68476-86-8	Petroleum gases, liquefied, sweetened
108-88-3	toluene
110-19-0	isobutyl acetate
108-10-1	4-methylpentan-2-one
78-93-3	butanone
763-69-9	ethyl 3-ethoxypropionate
108-65-6	2-methoxy-1-methylethyl acetate
2807-30-9	2-(propyloxy)ethanol
13463-67-7	titanium dioxide
1333-86-4	Carbon black
51274-00-1	YELLOW IRON OXIDE
67-56-1	methanol
1332-37-2	Iron oxide
7631-86-9	silicon dioxide, chemically prepared

· **Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1	4-methylpentan-2-one
13463-67-7	titanium dioxide
1333-86-4	Carbon black
1330-20-7	xylene
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

(Contd. on page 12)


Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 11)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

108-10-1 4-methylpentan-2-one

67-56-1 methanol

· Cancerogenity categories
· EPA (Environmental Protection Agency)

67-64-1 acetone

I

108-88-3 toluene

II

108-10-1 4-methylpentan-2-one

I

78-93-3 butanone

I

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone

A4

108-88-3 toluene

A4

13463-67-7 titanium dioxide

A4

1333-86-4 Carbon black

A4

1330-20-7 xylene

A4

100-41-4 ethylbenzene

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

1333-86-4 Carbon black

67-56-1 methanol

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms


GHS02



GHS04



GHS07



GHS08

· Signal word *Danger*
· Hazard-determining components of labeling:

toluene

acetone

4-methylpentan-2-one

butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container; May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

(Contd. on page 13)

USA



Trade name: 15003-15893 Color Coat Aerosol

(Contd. of page 12)

- H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.
- **Precautionary statements**
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P301+P310 If swallowed: Immediately call a poison center/doctor.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P321 Specific treatment (see on this label).
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Steve Gaver (sgaver@semproducts.com)
- **Date of preparation / last revision** 04/01/2015 / 13
- **Abbreviations and acronyms:**
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
 Carc. 2: Carcinogenicity, Hazard Category 2
 Repr. 2: Reproductive toxicity, Hazard Category 2
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- *** Data compared to the previous version altered.**