

1 Identification

· **Product identifier**

· **Trade name:** 19013 - 19483 Exterior Basecoat

· **Article number:**

19013, 19023, 19033, 19043, 19053, 19063, 19073, 19083, 19093, 19103, 19113, 19123, 19133, 19143, 19153, 19163, 19173, 19183, 19193, 19203, 19213, 19223, 19233, 19243, 19253, 19263, 19273, 19283, 19293, 19303, 19313, 19323, 19333, 19343, 19353, 19363, 19373, 19383, 19393, 19403, 19413, 19423, 19433, 19443, 19453, 19463, 19473, 19483

· **Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture** Coating

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225

· **Information department:**

cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)


Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 1)

· Hazard pictograms


GHS02 GHS04 GHS07 GHS08

· Signal word *Danger*
· Hazard-determining components of labeling:

 acetone
 toluene
 Carbon black
 n-butyl acetate

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:
· NFPA ratings (scale 0 - 4)


Health = 1

Fire = 4

Reactivity = 3

· HMIS-ratings (scale 0 - 4)


Health = *1

Fire = 4

Reactivity = 3

· Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

USA

(Contd. on page 3)



Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

67-64-1	acetone	40 - 60%
74-98-6	propane	13 - 30%
123-86-4	n-butyl acetate	13 - 30%
1330-20-7	xylene	1.5 - 5%
64742-88-7	Solvent naphtha (petroleum), medium aliph.	1.5 - 5%
108-65-6	2-methoxy-1-methylethyl acetate	1.5 - 5%
71-36-3	butan-1-ol	1.5 - 5%
108-88-3	toluene	1.5 - 5%
1333-86-4	Carbon black	≤1%
100-41-4	ethylbenzene	≤1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not gas tight seal receptacle.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm
	Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm
BEI	

74-98-6 propane

PEL	Long-term value: 1800 mg/m ³ , 1000 ppm
-----	--

(Contd. on page 5)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 4)

REL	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV	refer to Appendix F
123-86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm
1330-20-7 xylene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm
71-36-3 butan-1-ol	
PEL	Long-term value: 300 mg/m ³ , 100 ppm
REL	Ceiling limit value: 150 mg/m ³ , 50 ppm Skin
TLV	Long-term value: 61 mg/m ³ , 20 ppm
108-88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI
1333-86-4 Carbon black	
PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction
· Ingredients with biological limit values:	
67-64-1 acetone	
BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

(Contd. on page 6)

Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 5)

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 6)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44 °C

· **Flash point:** -97 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:	1.2 Vol %
Upper:	13.0 Vol %

· **Vapor pressure at 20 °C:** 8300 hPa

· **Density at 20 °C:** 0.78626 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **Solvent content:**

Organic solvents: 92.0 %

(Contd. on page 8)



Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 7)

VOC content:	48.0 % 671.4 g/l / 5.60 lb/gl
Solids content:	7.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
108-88-3	toluene	3
1333-86-4	Carbon black	2B
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 9)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 8)

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|---------------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1950 |
| · UN proper shipping name | |
| · DOT | Aerosols, flammable |
| · ADR | 1950 Aerosols |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |

- **Transport hazard class(es)**

- **DOT**



- | | |
|----------------|-----|
| · Class | 2.1 |
| · Label | 2.1 |

- **ADR**



- | | |
|----------------|------------|
| · Class | 2 5F Gases |
|----------------|------------|

(Contd. on page 10)

USA


Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 9)

 · **Label** 2.1

 · **IMDG, IATA**

 · **Class** 2.1

 · **Label** 2.1

 · **Packing group**

 · **DOT, ADR, IMDG, IATA** Void

 · **Environmental hazards:**

 · **Marine pollutant:** No

 · **Special precautions for user** Warning: Gases

 · **EMS Number:** F-D,S-U

 · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

 · **Transport/Additional information:**

 · **DOT**

 · **Quantity limitations** On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

 · **Remarks** ORM-D 49CFR 173-150,156,306

 · **ADR**

 · **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

 · **IMDG**

 · **Limited quantities (LQ)** 1L

 · **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

 · **UN "Model Regulation":** UN1950, Aerosols, 2.1

15 Regulatory information

 · **Safety, health and environmental regulations/legislation specific for the substance or mixture**

 · **Sara**

 · **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

 · **Section 313 (Specific toxic chemical listings):**

	ACRYLIC RESIN
1330-20-7	xylene
71-36-3	butan-1-ol
108-88-3	toluene
100-41-4	ethylbenzene

(Contd. on page 11)

USA



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 10)

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone
74-98-6	propane
123-86-4	n-butyl acetate
1330-20-7	xylene
64742-88-7	Solvent naphtha (petroleum), medium aliph.
108-65-6	2-methoxy-1-methylethyl acetate
71-36-3	butan-1-ol
108-88-3	toluene
1333-86-4	Carbon black
100-41-4	ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

1330-20-7	xylene
1333-86-4	Carbon black
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogen categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I
71-36-3	butan-1-ol	D
108-88-3	toluene	II
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
1330-20-7	xylene	A4
108-88-3	toluene	A4
1333-86-4	Carbon black	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 12)

Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 11)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

acetone
toluene
Carbon black
n-butyl acetate

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P211 Do not spray on an open flame or other ignition source.
P280 Wear protective gloves.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver (sgaver@semproducts.com)

· **Date of preparation / last revision** 04/01/2015 / 5

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 13)



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 19013 - 19483 Exterior Basecoat

(Contd. of page 12)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Carc. 2: Carcinogenicity, Hazard Category 2
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

· *** Data compared to the previous version altered.**

USA