Printing date 04/02/2015 Reviewed on 04/02/2015

1 Identification

- · Product identifier
- · Trade name: 2940-Series Sprayable Seam Sealers
- · Article number: 29462, 29472, 29482, 29492
- $\cdot \textit{Relevant identified uses of the substance or \textit{mixture and uses advised against}}$

No further relevant information available.

- · Application of the substance / the mixture Sealant
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

titanium dioxide

Proprietary Polymer

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

(Contd. on page 2)



Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: 2940-Series Sprayable Seam Sealers

(Contd. of page 1)

H335 May cause respiratory irritation.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P280 *Wear eye protection / face protection.*

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P312 Call a poison center/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH FIRE

Health = 1Fire = 1REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

| · Dangerous components: | | |
|-------------------------|--------------------------|----------|
| 1317-65-3 | GROUND CALCIUM CARBONATE | 60 - 70% |
| | Proprietary Polymer | |
| 13463-67-7 | titanium dioxide | 7 - 10% |
| 1333-86-4 | Carbon black | ≤1% |

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

SEM

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: 2940-Series Sprayable Seam Sealers

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

USA

SEM

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: 2940-Series Sprayable Seam Sealers

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:

13463-67-7 titanium dioxide

PEL Long-term value: 15* mg/m³

*total dust

REL See Pocket Guide App. A

TLV Long-term value: 10 mg/m³ withdrawn from NIC

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

(Contd. on page 5)

SEM

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: 2940-Series Sprayable Seam Sealers

| | (Contd. of pag |
|--------------------------------------|--|
| Color: | According to product specification |
| Odor: | Characteristic |
| · Odour threshold: | Not determined. |
| pH-value: | Not applicable. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 2501 °C |
| · Flash point: | 98 °C |
| Flammability (solid, gaseous): | Not determined. |
| · Ignition temperature: | 270 °C |
| Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| Danger of explosion: | Product does not present an explosion hazard. |
| | In use, may form flammable/explosive vapour-air mixture. |
| Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| · Vapor pressure at 20 °C: | 23 hPa |
| Density at 20 °C: | 1.06 g/cm³ |
| · Relative density | Not determined. |
| · Vapour density | Not applicable. |
| Evaporation rate | Not applicable. |
| Solubility in / Miscibility with | |
| Water: | Insoluble. |
| Partition coefficient (n-octanol/wat | ter): Not determined. |
| · Viscosity: | |
| Dynamic: | Not applicable. |
| Kinematic: | Not applicable. |
| Solvent content: | |
| Organic solvents: | 0.0 % |
| VOC content: | g/l / 1.24 lb/gl |
| Solids content: | 100.0 % |
| Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)



Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: 2940-Series Sprayable Seam Sealers

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

| | caremogen | ic cure gories | |
|---|---|--------------------------------------|------------|
| | · IARC (International Agency for Research on Cancer) | | |
| | 13463-67-7 | titanium dioxide | 2 <i>B</i> |
| ı | 1333-86-4 | Carbon black | 2B |
| | 7631-86-9 | silicon dioxide, chemically prepared | 3 |
| | · NTP (National Toxicology Program) | | |
| | None of the ingredients is listed. | | |
| | · OSHA-Ca (Occupational Safety & Health Administration) | | |
| | None of the ingredients is listed. | | |
| | | | |

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

SEM

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: 2940-Series Sprayable Seam Sealers

(Contd. of page 6)

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

| UN-Number DOT, ADR, ADN, IMDG, IATA | Void | |
|---|---------------------------------|--|
| UN proper shipping name DOT, ADR, ADN, IMDG, IATA | Void | |
| Transport hazard class(es) | | |
| DOT, ADR, ADN, IMDG, IATA Class | Void | |
| Packing group DOT, ADR, IMDG, IATA | Void | |
| Environmental hazards: Marine pollutant: | No | |
| Special precautions for user | Not applicable. | |
| Transport in bulk according to Annex MARPOL73/78 and the IBC Code | II of Not applicable. | |
| UN ''Model Regulation'': | - · · | |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

| · Section 355 | (extremely | hazardous | substances): | |
|---------------|------------|-----------|--------------|--|
|---------------|------------|-----------|--------------|--|

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

1317-65-3 GROUND CALCIUM CARBONATE

13463-67-7 titanium dioxide

1333-86-4 Carbon black

7631-86-9 silicon dioxide, chemically prepared

21645-51-2 aluminium hydroxide

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7 titanium dioxide

1333-86-4 Carbon black

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 8)



Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: 2940-Series Sprayable Seam Sealers

| | (Contd. of page 7) |
|--|--------------------|
| · Chemicals known to cause reproductive toxicity for males: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause developmental toxicity: | |
| None of the ingredients is listed. | |
| · Cancerogenity categories | |
| · EPA (Environmental Protection Agency) | |
| None of the ingredients is listed. | |
| · TLV (Threshold Limit Value established by ACGIH) | |
| 13463-67-7 titanium dioxide | A4 |
| 1333-86-4 Carbon black | A4 |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | |
| 13463-67-7 titanium dioxide | |
| 1333-86-4 Carbon black | |

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

titanium dioxide

Proprietary Polymer

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P312 Call a poison center/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

HC

SEM

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: 2940-Series Sprayable Seam Sealers

(Contd. of page 8)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Steve Gaver (sgaver@semproducts.com)
- · Date of preparation / last revision 04/02/2015 / 3
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* * Data compared to the previous version altered.

USA ·