

## 1 Identification

- **Product identifier**
- **Trade name:** 38203 Guide Coat Black
- **Article number:** 38203
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Carc. 2	H351	Suspected of causing cancer.
Repr. 2	H361	Suspected of damaging fertility or the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

**Trade name: 38203 Guide Coat Black**

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*toluene  
acetone  
ethyl acetate  
butanone*

· **Hazard statements**

*H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.*

· **Precautionary statements**

*P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 Specific treatment (see on this label).  
P405 Store locked up.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**3 Composition/information on ingredients**

· **Chemical characterization: Mixtures**

· **Description:**

*Mixture: consisting of the following components.  
Weight percentages*

(Contd. on page 3)



Printing date 04/01/2015

Reviewed on 04/01/2015

**Trade name: 38203 Guide Coat Black**

(Contd. of page 2)

**· Dangerous components:**

67-64-1	acetone	40 - 60%
68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
108-88-3	toluene	13 - 30%
141-78-6	ethyl acetate	7 - 10%
78-93-3	butanone	1-1.5%
1333-86-4	Carbon black	≤1%

**4 First-aid measures**

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

USA

(Contd. on page 4)



Trade name: 38203 Guide Coat Black

(Contd. of page 3)

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

### 67-64-1 acetone

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m<sup>3</sup>, (750) NIC-500 ppm

Long-term value: (1188) NIC-594 mg/m<sup>3</sup>, (500) NIC-250 ppm

BEI

### 108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500\* ppm

\*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm

Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm

BEI

### 141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm

(Contd. on page 5)

USA



**Trade name: 38203 Guide Coat Black**

(Contd. of page 4)

REL	Long-term value: 1400 mg/m <sup>3</sup> , 400 ppm
TLV	Long-term value: 1440 mg/m <sup>3</sup> , 400 ppm
<b>78-93-3 butanone</b>	
PEL	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm BEI
<b>· Ingredients with biological limit values:</b>	
<b>67-64-1 acetone</b>	
BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
<b>108-88-3 toluene</b>	
BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene  0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
<b>78-93-3 butanone</b>	
BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

**Trade name: 38203 Guide Coat Black**

(Contd. of page 5)

· **Protection of hands:**

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*



*Protective gloves*

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**



*Tightly sealed goggles*

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Aerosol
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	55 °C

· **Flash point:** -103 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 460 °C

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	13.0 Vol %

(Contd. on page 7)



Trade name: 38203 Guide Coat Black

(Contd. of page 6)

· Vapor pressure at 20 °C:	233 hPa
· Density at 20 °C:	0.75147 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	94.5 %
VOC content:	47.5 %
	645.8 g/l / 5.39 lb/gl
· Solids content:	5.8 %
· Other information	No further relevant information available.

\*

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### 108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

(Contd. on page 8)





Printing date 04/01/2015

Reviewed on 04/01/2015

**Trade name: 38203 Guide Coat Black**

(Contd. of page 7)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
1330-20-7	xylene	3
1333-86-4	Carbon black	2B
111-76-2	2-butoxyethanol	3
68855-54-9	Kieselguhr, soda ash flux-calcined	GROUP 1
9002-88-4	POLYETHYLENE	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

68855-54-9	Kieselguhr, soda ash flux-calcined	HUMAN CARCINOGEN
------------	------------------------------------	------------------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN1950

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS



Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: 38203 Guide Coat Black

(Contd. of page 8)

· **UN proper shipping name**  
 · **DOT** Aerosols, flammable  
 · **ADR** 1950 Aerosols  
 · **IMDG** AEROSOLS  
 · **IATA** AEROSOLS, flammable

· **Transport hazard class(es)**· **DOT**

· **Class** 2.1  
 · **Label** 2.1

· **ADR**

· **Class** 2 5F Gases  
 · **Label** 2.1

· **IMDG, IATA**

· **Class** 2.1  
 · **Label** 2.1

· **Packing group**· **DOT, ADR, IMDG, IATA** Void· **Environmental hazards:**· **Marine pollutant:** No· **Special precautions for user** Warning: Gases· **EMS Number:** F-D,S-U

· **Transport in bulk according to Annex II of  
 MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 75 kg  
 On cargo aircraft only: 150 kg

· **ADR**

· **Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity

(Contd. on page 10)

USA



Printing date 04/01/2015

Reviewed on 04/01/2015

**Trade name: 38203 Guide Coat Black**

(Contd. of page 9)

- |                                   |  |
|-----------------------------------|--|
| · <b>IMDG</b>                     |  |
| · <b>Limited quantities (LQ)</b>  | 1L   |
| · <b>Excepted quantities (EQ)</b> | Code: E0<br>Not permitted as Excepted Quantity |
| · <b>UN "Model Regulation":</b>   | UN1950, Aerosols, 2.1                          |

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

### · **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

### · **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
	ACRYLIC RESIN
78-93-3	butanone
1330-20-7	xylene
111-76-2	2-butoxyethanol
67-56-1	methanol
100-41-4	ethylbenzene

### · **TSCA (Toxic Substances Control Act):**

67-64-1	acetone
68476-86-8	Petroleum gases, liquefied, sweetened
108-88-3	toluene
141-78-6	ethyl acetate
78-93-3	butanone
123-86-4	n-butyl acetate
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
1330-20-7	xylene
1333-86-4	Carbon black
68611-44-9	Silane Modified Silica
111-76-2	2-butoxyethanol
68855-54-9	Kieselguhr, soda ash flux-calcined
9002-88-4	POLYETHYLENE
67-56-1	methanol
100-41-4	ethylbenzene

### · **Proposition 65**

#### · **Chemicals known to cause cancer:**

1330-20-7	xylene
1333-86-4	Carbon black
68855-54-9	Kieselguhr, soda ash flux-calcined

(Contd. on page 11)

**Trade name: 38203 Guide Coat Black**

(Contd. of page 10)

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.	
------------------------------------	--

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

67-56-1	methanol
---------	----------

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
108-88-3	toluene	II
78-93-3	butanone	I
1330-20-7	xylene	I
111-76-2	2-butoxyethanol	NL
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
1330-20-7	xylene	A4
1333-86-4	Carbon black	A4
111-76-2	2-butoxyethanol	A3
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
67-56-1	methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02   GHS04   GHS07   GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene

acetone

ethyl acetate

butanone

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

(Contd. on page 12)



**Trade name: 38203 Guide Coat Black**

(Contd. of page 11)

- H361 Suspected of damaging fertility or the unborn child.*
- H336 May cause drowsiness or dizziness.*
- H373 May cause damage to organs through prolonged or repeated exposure.*
- H304 May be fatal if swallowed and enters airways.*
- **Precautionary statements**
  - P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
  - P251 Pressurized container: Do not pierce or burn, even after use.*
  - P260 Do not breathe dust/fume/gas/mist/vapors/spray.*
  - P301+P310 If swallowed: Immediately call a poison center/doctor.*
  - P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
  - P321 Specific treatment (see on this label).*
  - P405 Store locked up.*
  - P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*
  - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environment protection department.
- **Contact:** Steve Gaver (sgaver@semproducts.com)
- **Date of preparation / last revision** 04/01/2015 / 3
- **Abbreviations and acronyms:**
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
  - ICAO: International Civil Aviation Organisation*
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
  - IMDG: International Maritime Code for Dangerous Goods*
  - DOT: US Department of Transportation*
  - IATA: International Air Transport Association*
  - ACGIH: American Conference of Governmental Industrial Hygienists*
  - EINECS: European Inventory of Existing Commercial Chemical Substances*
  - ELINCS: European List of Notified Chemical Substances*
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)*
  - NFPA: National Fire Protection Association (USA)*
  - HMIS: Hazardous Materials Identification System (USA)*
  - VOC: Volatile Organic Compounds (USA, EU)*
  - LC50: Lethal concentration, 50 percent*
  - LD50: Lethal dose, 50 percent*
  - Flam. Aerosol 1: Flammable aerosols, Hazard Category 1*
  - Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*
  - Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A*
  - Carc. 2: Carcinogenicity, Hazard Category 2*
  - Repr. 2: Reproductive toxicity, Hazard Category 2*
  - STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*
  - STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2*
  - Asp. Tox. 1: Aspiration hazard, Hazard Category 1*
- **\* Data compared to the previous version altered.**