SAFETY DATA SHEET

AA607

Section 1. Identification

Product name : Accelerator **Product code** : AA607 Other means of Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : Valspar Automotive

101 W. Prospect Ave., Cleveland, OH 44115

USA

Emergency telephone number of the company

: US / Canada: (216) 566-2917

Mexico: 55-4160-8800 / 55-4160-8819 Monday to Friday from 8:30 a.m. to 5:30 p.m.

Product Information Telephone Number

: US / Canada: 1-800-844-3691 Option 3

Mexico: 55-5333-1500

Transportation Emergency

: US / Canada: (800) 424-9300

Telephone Number

Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1

GERM CELL MUTAGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 1.1%

(dermal), 1.1% (inhalation)

GHS label elements

Hazard pictograms









Signal word : Danger

Date of issue/Date of revision : 4/29/2025 Date of previous issue : 3/24/2025 Version : 2.02 1/16 AA607 Accelerator SHW-85-NA-GHS-US

Section 2. Hazards identification

Hazard statements

: Flammable liquid and vapor.

Harmful if swallowed.

Toxic in contact with skin or if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Suspected of causing genetic defects.

May damage fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response

: IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor. IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage Disposal

Store locked up.

: Dispose of contents and container in accordance with all local, regional, national and international regulations

international regulations.

Supplemental label

elements

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. FOR PROFESSIONAL USE ONLY.

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise

classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

CAS number/other identifiers

Ingredient name	% by weight	Identifiers
2,4-Pentanedione	≥90	123-54-6
Dibutyltin Dilaurate	≤1.8	77-58-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision: 4/29/2025Date of previous issue: 3/24/2025Version: 2.022/16AA607AcceleratorSHW-85-NA-GHS-US

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention. If necessary, call a poison center or physician.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. In the event of any complaints or symptoms, avoid further

exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. If material has been swallowed

and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention

immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt

or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Toxic if inhaled. Causes damage to organs following a single exposure if inhaled.

Skin contact: Toxic in contact with skin. Causes damage to organs following a single exposure in

contact with skin. Causes skin irritation. May cause an allergic skin reaction.

Ingestion: Harmful if swallowed. Causes damage to organs following a single exposure if

swallowed.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date of revision : 4/29/2025 Date of previous issue : 3/24/2025 Version : 2.02 3/16

AA607 Accelerator SHW-85-NA-GHS-US

Section 4. First aid measures

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Remark : Flammable liquid.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions:

Date of issue/Date of revision: 4/29/2025Date of previous issue: 3/24/2025Version: 2.024/16AA607AcceleratorSHW-85-NA-GHS-US

Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

 Date of issue/Date of revision
 : 4/29/2025
 Date of previous issue
 : 3/24/2025
 Version
 : 2.02
 5/16

 AA607
 Accelerator
 SHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection

Ingredient name	CAS#	Exposure limits
2,4-Pentanedione	123-54-6	ACGIH TLV (United States, 1/2024) Absorbed through skin. TWA 8 hours: 25 ppm.
Dibutyltin Dilaurate	77-58-7	ACGIH TLV (United States, 1/2024) [Tin, organic compounds] A4. Absorbed through skin. TWA 8 hours: 0.1 mg/m³ (as Sn). STEL 15 minutes: 0.2 mg/m³ (as Sn). NIOSH REL (United States, 10/2020) [tin organic compounds] Absorbed through skin. TWA 10 hours: 0.1 mg/m³ (as Sn). OSHA PEL (United States, 5/2018) [Tin, organic compounds] TWA 8 hours: 0.1 mg/m³ (as Sn).

Occupational exposure limits (Canada)

Ingredient name	CAS#	Exposure limits
2,4-Pentanedione	123-54-6	CA British Columbia Provincial (Canada, 4/2024) Absorbed through skin. Notes: No British Columbia exposure limit at this time CA Ontario Provincial (Canada, 6/2019) Absorbed through skin. TWA 8 hours: 25 ppm.
Dibutyltin dilaurate	77-58-7	CA Saskatchewan Provincial (Canada, 4/2021) [Tin organic compounds] Absorbed through skin. STEL 15 minutes: 0.2 mg/m³ (measured as Sn). TWA 8 hours: 0.1 mg/m³ (measured as Sn). CA British Columbia Provincial (Canada, 4/2024) [tin - organic compounds] Absorbed through skin. TWA 8 hours: 0.1 mg/m³ (as Sn). STEL 15 minutes: 0.2 mg/m³ (as Sn). CA Ontario Provincial (Canada, 6/2019) [Tin (Organic compounds)] Absorbed through skin. TWA 8 hours: 0.1 mg/m³ (as Sn). CA Alberta Provincial (Canada, 3/2023) [Tin Organic compounds] Absorbed through skin. OEL 15 minutes: 0.2 mg/m³ (as Sn). OEL 8 hours: 0.1 mg/m³ (as Sn).

Occupational exposure limits (Mexico)

Date of issue/Date of revision: 4/29/2025Date of previous issue: 3/24/2025Version: 2.026/16AA607AcceleratorSHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection

Ingredient name	CAS#	Exposure limits
2,4-Pentanedione	123-54-6	NOM-010-STPS-2014 (Mexico, 4/2016) Absorbed through skin. TWA 8 hours: 20 ppm.
Dibutyltin Dilaurate	77-58-7	NOM-010-STPS-2014 (Mexico, 4/2016) [Estaño, compuestos orgánicos] A4. Absorbed through skin. TWA 8 hours: 0.1 mg/m³ (as Sn). STEL 15 minutes: 0.2 mg/m³ (as Sn).

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

 Date of issue/Date of revision
 : 4/29/2025
 Date of previous issue
 : 3/24/2025
 Version
 : 2.02
 7/16

 AA607
 Accelerator
 SHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection

: Appropriate footwear and any additional skin protection measures should be selected Other skin protection

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory protection Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid. Color : Clear.

: Not available. Odor **Odor threshold** : Not available. : Not applicable. Melting point/freezing point : Not available. : 140°C (284°F) **Boiling point or initial**

boiling point and boiling

range

Flash point : Closed cup: 36°C (96.8°F) [Pensky-Martens Closed Cup]

Evaporation rate : 0.75 (butyl acetate = 1) **Flammability** : Flammable liquid. : Lower: 2.4%

Lower and upper explosion limit/flammability limit

: 0.93 kPa (7 mm Hg)

Upper: 11.4%

Relative vapor density

: 3.5 [Air = 1] Relative density 0.97

: 0.97 g/cm³ **Density**

Solubility(ies)

Media	Result
cold water	Not soluble

Partition coefficient: n-

octanol/water

Viscosity

Vapor pressure

: Not applicable.

Auto-ignition temperature

: Not available. : Not available.

Decomposition temperature

Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available.

Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)

Molecular weight Not applicable.

Particle characteristics

Median particle size : Not applicable. **Heat of combustion** : 43.7 kJ/g

Date of issue/Date of revision : 4/29/2025 Date of previous issue : 3/24/2025 Version : 2.02 8/16 AA607 Accelerator SHW-85-NA-GHS-US

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not

allow vapor to accumulate in low or confined areas.

Incompatible materials: Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name Result

2,4-Pentanedione Rat - Oral - LD50

55 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed

activity) Behavioral - Rigidity (including catalepsy)

Dibutyltin Dilaurate Rat - Oral - LD50

2071 mg/kg

Conclusion/Summary [Product] : Not available.

Skin corrosion/irritation

Dibutyltin Dilaurate

Product/ingredient name Result

2,4-Pentanedione Rabbit - Skin - Mild irritant

Amount/concentration applied: 488 mg

Rabbit - Skin - Mild irritant

<u>Duration of treatment/exposure</u>: 6 hours <u>Amount/concentration applied</u>: 11.2 MI I **Rabbit - Skin - Moderate irritant**

<u>Duration of treatment/exposure</u>: 48 hours <u>Amount/concentration applied</u>: 11.2 MI I

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 6 hours

Amount/concentration applied: 33.6 MI

Rabbit - Skin - Severe irritant

Amount/concentration applied: 500 mg

Conclusion/Summary [Product]: Not available.

Serious eye damage/eye irritation

Product/ingredient name Result

Date of issue/Date of revision : 4/29/2025 Date of previous issue : 3/24/2025 Version : 2.02 9/16

AA607 Accelerator SHW-85-NA-GHS-US

Section 11. Toxicological information

2,4-Pentanedione Rabbit - Eyes - Severe irritant

Amount/concentration applied: 20 mg
Rabbit - Eyes - Severe irritant
Amount/concentration applied: 0.1 MI

Dibutyltin Dilaurate Rabbit - Eyes - Moderate irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 100 mg

Conclusion/Summary [Product]: Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name Result

Dibutyltin Dilaurate SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 1

Specific target organ toxicity (repeated exposure)

Product/ingredient name Result

Date of issue/Date of revision : 4/29/2025 Date of previous issue : 3/24/2025 Version : 2.02 10/16

AA607 Accelerator SHW-85-NA-GHS-US

Section 11. Toxicological information

Dibutyltin Dilaurate

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (oral) - Category 1

Aspiration hazard

Not available.

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Toxic if inhaled. Causes damage to organs following a single exposure if inhaled.

Skin contact: Toxic in contact with skin. Causes damage to organs following a single exposure in

contact with skin. Causes skin irritation. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed. Causes damage to organs following a single exposure if

swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

 Date of issue/Date of revision
 : 4/29/2025
 Date of previous issue
 : 3/24/2025
 Version
 : 2.02
 11/16

 AA607
 Accelerator
 SHW-85-NA-GHS-US

Section 11. Toxicological information

General : Causes damage to organs through prolonged or repeated exposure. Once sensitized,

a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Accelerator 2,4-Pentanedione Dibutyltin Dilaurate	504.3	303.4	N/A	3.0	N/A
	500	300	N/A	3	N/A
	2071	N/A	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name Result

2,4-Pentanedione Acute - LC50 - Fresh water

Daphnia - Water flea - Daphnia magna - Neonate

Age: 0 to 24 hours 47.6 mg/l [48 hours] Effect: Mortality

Acute - LC50 - Fresh water

Fish - Bluegill - Lepomis macrochirus

Weight: 0.47 g 60.1 mg/l [96 hours] Effect: Mortality

Dibutyltin Dilaurate Chronic - EC10 - Fresh water

Algae - Green algae - Desmodesmus subspicatus

>2 mg/l [96 hours] Effect: Histology

Conclusion/Summary [Product] : Not available.

Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Dibutyltin Dilaurate	-	2.91	Low

Mobility in soil

 Date of issue/Date of revision
 : 4/29/2025
 Date of previous issue
 : 3/24/2025
 Version
 : 2.02
 12/16

 AA607
 Accelerator
 SHW-85-NA-GHS-US

Section 12. Ecological information

Soil/Water partition coefficient

: Not available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN2310	UN2310	UN2310	UN2310	UN2310
UN proper shipping name	PENTANE- 2,4-DIONE solution	PENTANE- 2,4-DIONE solution	PENTANE- 2,4-DIONE solution	PENTANE- 2,4-DIONE solution	PENTANE- 2,4-DIONE solution
Transport hazard class(es)	3 (6.1)	3 (6.1)	3 (6.1)	3 (6.1)	3 (6.1)
Packing group	III	III	Ш	III	III
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.26-2.36 (Class 6).	-	-	Emergency schedules F-E, S-D

Date of issue/Date of revisionAA607 Accelerator

: 4/29/2025 Date of previous issue

: 3/24/2025

Version : 2.02

13/16

SHW-85-NA-GHS-US

Section 14. Transport information ERG No. ERG No. ERG No. 131 131 131

Special precautions for user :

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according: Not available.

to IMO instruments

Proper shipping name : Not available.

Section 15. Regulatory information

U.S. Federal regulations

TSCA 12(b) - Chemical export notification

	One time notification		Annual notification		
Name	4	5	5(f)	6	7
2,4-Pentanedione	Not listed	Listed	Not listed	Not listed	Not listed \

California Prop. 65

Not applicable.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed

International lists

: Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Taiwan Chemical Substances Inventory (TCSI): Not determined.

Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Date of issue/Date of revision : 4/29/2025 Date of previous issue : 3/24/2025 Version : 2.02 14/16 SHW-85-NA-GHS-US

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
ACUTE TOXICITY (oral) - Category 4	Calculation method
ACUTE TOXICITY (dermal) - Category 3	Calculation method
ACUTE TOXICITY (inhalation) - Category 3	Calculation method
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
GERM CELL MUTAGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method

History

Date of printing : 4/29/2025 Date of issue/Date of : 4/29/2025

revision

Date of previous issue : 3/24/2025

Version : 2.02

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

▼ Indicates information that has changed from previously issued version.

Notice to reader

 Date of issue/Date of revision
 : 4/29/2025
 Date of previous issue
 : 3/24/2025
 Version
 : 2.02
 15/16

 AA607
 Accelerator
 SHW-85-NA-GHS-US

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buver/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

 Date of issue/Date of revision
 : 4/29/2025
 Date of previous issue
 : 3/24/2025
 Version
 : 2.02
 16/16

 AA607
 Accelerator
 SHW-85-NA-GHS-US